

DMS-GF/HF Series (RS-232, RS-422) Overview

Model Number	Modulation Frequency	Transmission Direction & Distance	Interface
DMS-GF1A-02	Transmission 5.5MHz Reception 6.0MHz	Head-on, 1-meter range	RS-232
DMS-GF1B-02	Transmission 6.0MHz Reception 5.5MHz	Head-on, 1-meter range	RS-232
DMS-HF1A-02	Transmission 5.5MHz Reception 6.0MHz	Side-on, 1-meter range	RS-232
DMS-HF1B-02	Transmission 6.0MHz Reception 5.5MHz	Side-on, 1-meter range	RS-232
DMS-GF2A-02	Transmission 5.5MHz Reception 6.0MHz	Head-on, 3-meter range	RS-232
DMS-GF2B-02	Transmission 6.0MHz Reception 5.5MHz	Head-on, 3-meter range	RS-232
DMS-HF2A-02	Transmission 5.5MHz Reception 6.0MHz	Side-on, 3-meter range	RS-232
DMS-HF2B-02	Transmission 6.0MHz Reception 5.5MHz	Side-on, 3-meter range	RS-232
DMS-GF1A-12	Transmission 5.5MHz Reception 6.0MHz	Head-on, 1-meter range	RS-422
DMS-GF1B-12	Transmission 6.0MHz Reception 5.5MHz	Head-on, 1-meter range	RS-422
DMS-HF1A-12	Transmission 5.5MHz Reception 6.0MHz	Side-on, 1-meter range	RS-422
DMS-HF1B-12	Transmission 6.0MHz Reception 5.5MHz	Side-on, 1-meter range	RS-422
DMS-GF2A-12	Transmission 5.5MHz Reception 6.0MHz	Head-on, 3-meter range	RS-422
DMS-GF2B-12	Transmission 6.0MHz Reception 5.5MHz	Head-on, 3-meter range	RS-422

****** For detailed product specifications please visit the Downloads section of our website.**